



### Fire Key

- Main Panel
- Emergency lighting (maintained) to give 0.5 lux minimum to BS5266 Pt. 7/EN1838 - 4.3
- Integral emergency lighting (maintained) to give 1 lux minimum to BS5266 Pt. 1
- Lighted directional signage with integral emergency lighting (maintained) or maintained lighting above
- Call point
- Sounder
- Smoke detector
- Heat detector
- CO2
- Foam extinguisher
- Fire Blanket
- Emergency Door Release

### KEY

- Single pole one way switch
- Multi switch
- Two-way switch
- Cord operated one-way switch
- Rheostat or dimmer switch
- PIR
- Down Lighter
- Ceiling Light
- Wall light
- Bulk Head Light
- Single tube fluorescent
- Spot Light
- Fuse spur
- Single Socket
- Multi Socket
- Multi Socket with USB sockets
- Radiant wall heater
- Aerial
- Fan
- Meter
- Mainswitch/Distribution
- Telecom
- Cat 6 network jack
- Fan switch

REV	DATE

**PSK**  
architect  
*New Build & Commercial Architect*

TITLE

**Commercial Unit  
CHELTENHAM**

DESCRIPTION

**SHEET 1 OF 2**

DATE	SCALE
05/11/2021	1/100
DRAWN	CHECKED
A. Davis	-----

DRAWING NO.

**CC50 PSK 00**

